

## **ECO Lines F150**

**ECO Lines F150 High Power LED Line Projector** 

Projects a thick, permanent floor line that eliminates the need for maintenance required by floor tape and paint lines.

- 3rd Generation: Crisper, longer lines at increased brightness
- Designed for Rugged Environments and long service life
- Focusable for optimal line appearance and brightness
- Maintenance free, no fans or motors
- Adjustable line length option



## **SPECIFICATIONS**

Item Codes: EL-F150Y (yellow), EL-F150A (amber), EL-F150G (green), EL-F150B (blue), EL-F150R (red), EL-F150W (white)

Power Supply: 100-240/277VAC, 50/60Hz (Voltage Range: 90-305VAC, 48-63Hz; 127-431VDC)

Power Draw: 140W, 1.6A/115V, 0.7A/277V

Driver: MOSO X6-150M041 (integrated)

Inrush Current: COLD START 75A (t width=570µs at 50% I peak) at 230VAC per NEMA 410

Breakers: We recommend lighting specific breakers at 70% of specified load

Power Cord: Length: 8.5' (2.6m), Plug: Standard plug: Nema 5-15 (other plug options available)

Control Input Signals: On/Off or Dimming: 1-10V, 10-100KOhm, PWM, Dry Switch

Environmental Rating: Driver: IP67, Projector: IP65

Safety Standards: EC: EN IEC 60598-1:2021, N IEC 60598-2-1:2021, Driver: UL E334687

Temperature Range: -22°F to 113°F (-30°C to 45°C)

LED Life: 35,000h until 30% brightness loss is reached (L70\*) (\*L70= the time to 30% brightness loss)

Driver Life: MTBF: 200,000h, lifetime: 100,000h at tc=75°C and 80% load (driver and LED are field serviceable)

Projection Colors: Yellow, Green, Red, Blue, Amber, White (colors are changeable by swapping the LED)

Line Width: 3 to 6" (75 to 150mm)

Projection Lenses: 53° (1:0.93 throw ratio) 73° (1:1.4 throw ratio) 90° (1:1.86 throw ratio) Focus: Field adjustable focus, pre-set for 21-33' (6.4-9.5m) projection distance.

Typ. Projection Range / Size Bright Environment Average Env. Dim Env.

Typ. Usable Line Length: 36-45' (11-14m) 48-56' (15-17m) 80' (24m)

At typ. Distance: 20/27/41' (6/8/13m) 26/34/52' (7.5/10/15m) 43/65/86' (12/16/24m)

Line Length Adjustment: Yes, with optional blinders (the min. length is approx. 30% of the full line length)

Product Warranty: Two years from date of purchase

Copyright ©2025 Globus New Media LLC, Specifications may change at any time, not liable for errors or omissions

V05062025